


HCVB2 Valve



Application

Regulatory valve of HCVB2 type is ready to perform with heavy erosive media. It is suitable to control the highly demanding parameters, also during infinite critical conditions. Advantage of this valve is high coefficient of the pressure recycling. It perfectly fits if the reduction of noise and/or cavitation are of extreme importance.

Description

HCVB2 is straightway valve. Basically, it consists of body topped by the bonnet and the seat fixed by throttled cages: active (which drives a plug) and passive one. Both the bonnet and the seat, as well as active cage, are sealed with graphite spiral wound gaskets (placed in channels). Thus, disassembly and assembly of the valve are easy and do not require any special tools. A medium undergoes two-step expansion (when the plug is of piston-type) or three-step expansion (when perforated plug is applied). Piston-type plug exposes vents of the cage and gives the way to the partial expansion. Further reduction of the pressure is up to vents of the passive cage. The valve with perforated plug allows for the allocation of pressure drop first to the plug itself (active stage) and next to two throttle cages (both are passive ones). Plug of HCVB2 valve can be balanced by means of seal. Thanks to that the lower power of the actuator is needed. The valve with seal balanced plug resides in class IV leakage allowable. HCVB2 valve works with media flow directed under the plug.

Technical data

Nominal diameter	DN25÷DN300			
Nominal pressure	PN10÷PN400			
Connections	bolted flanges; welding ready			
Flow coefficient Kvs	10÷1300 m ³ /h			
Body	1.0460 (P250GH) 1.0619 (GP240GH) 1.5415 (16Mo3) 1.7335 (13CrMo4-5)	1.5419 (G20Mo5) 1.7357 (G17CrMo5-5) 1.4541 (X6CrNiTi18-10) 1.4404 (X2CrNiMo17-12-2)	1.4308 (GX5CrNi19-10) 1.4408 (GX5CrNiMo19-11-2) 1.7380 (10CrMo9-10) 1.7715 (14MoV6-3)	1.4903 (X10CrMoVNb9-1) 1.4901 (X10CrWMoVNb9-2) 1.7379 (G17CrMo9-10) 1.6368 (15NiCuMoNb5-6-4)
Plug	1.4541 (X6CrNiTi18-10)	1.4057 (X17CrNi16-2)	1.4125 (X105CrMo17)	titanium BT-9
Seat	1.4541 (X6CrNiTi18-10)	1.4057 (X17CrNi16-2)	1.4125 (X105CrMo17)	titanium BT-9
Stem	1.4057 (X17CrNi16-2)	1.4923 (X22CrMoV12-2)		
Cages	1.4057 (X17CrNi16-2)			
Hardening of the inner parts	stellite; nitriding; hardening			
Rangeability	50:1			
Leakage class	metal/metal sealing – IV (standard); V (improved)			
Body's gland	spiral, metal+graphite			
Seal bushing	graphite; PTFE			

INTEC

Industrial Automatics Enterprise INTEC Ltd. Co.
ul. Bacciarlego 54, 51-649 Wrocław, Poland
tel./fax: + 48 71 348 18 18, e-mail: biuro@intec.com.pl
www.intec.com.pl

WK

WAKMET Industrial Valves Factory Ultd.
Bodzanów 75, 48-340 Gluchotazy 1, Poland
tel./fax: + 48 77 439 40 20, e-mail: wakmet@wakmet.com.pl
www.wakmet.com.pl