


# MCV GLOBE CONTROL VALVE TECHNICAL BRIEF

	Client:	Quotation No:	Valve desc:	KKS:	Valve specification:
---	---------	---------------	-------------	------	----------------------



Medium Trimmed Globe Control Valves **MCV** type are suitable in applications where liquids, steam and gases flow are to be controlled. The range of materials and design options makes the valves applicable in medium working conditions – PN40+PN160, T(-50+560°C) without heavy cavitation, flashing or choked flow. If there is a risk that any of that phenomena appears then external protect devices like orifices or direct diffusers should be installed. The valve is globe type with cast body and screwed seat. **FTO flow direction is strongly recommended**, specially when profiled plug.

### Benefits:

- Interchangeable trim designs
- Metal to metal planned bonnet with spiral gasket
- High rangeability available
- High leakage class available
- Balanced trim design available
- Easy maintenance
- Butt weld ends / flange connection matching the pipe size
- All actuator systems are adaptable

**Alternative solutions:** Economic- **ECV** type valves, higher performance- **HVC** type valves.

Rangeability:	1:50 (standard), 1:100 (option)
Profiled plug 100% open- main coefficients	FL=0.9; XT=0.72; Fd=0.46; xFz=0.65
Perforated plug 100% open- main coefficients	FL=0.95; XT=0.78; Fd=0.1; xFz=0.75


Kvs	Stroke	Seat diam.C	Seat diam.P	DN min	DN max
0,1	20	6	-	15	50
0,16	20	6	-	15	50
0,25	20	6	-	15	50
0,4	20	6	-	15	50
0,63	20	6	-	15	50
1	20	9	9	15	50
1,6	20	9	14	15	50
2,5	20	14	14	15	50
4	20	14	19	15	50
6,3	20	19	19	20	50
10	20	19	25	25	50
16	20	25	34	32	65
25	20	34	44	40	80
40	20	44	50	50	100
63	40	50	70	65	150
94	40	70	90	80	200
125	40	90	100	100	250
160	40	100	110	125	250
250	50	110	125	150	250
320	50	125	160	150	250
500	63	160	194	200	300
630	63	194	194	200	300
800	100	194	240	250	300
1000	100	240	240	300	300
1300	100	240	270	300	300

C – profiled plug , P – perforated plug

Part No	Part Name	Specification. position	Symbol	Material/performance	Part No	Part Name	Specification. position	Symbol	Material/performance
1	Plug	X1 Performance	C	Profiled	5	Body	X8 Performance	1	DIN/PN Flanged
			P	Perforated				2	ANSI Flanged
		X2 Ballancing	U	Unbalanced			3	BW Standard	
			B	Balanced			4	BW Specified	
		X3 Material	1	1.4571			1	1.0460, DN15-50	
			2	1.4571+stellite			2	1.0619	
			3	1.4571+nitrogen			3	1.5415, DN15-50	
			4	1.4057 hard. 35 HRC			4	1.7335, DN15-40	
			5	1.4125 hard. 55 HRC			5	1.5419	
			33	Other			6	1.7357	
			L	Linear			7	1.4541, DN15-50	
		X4 Characteristic	P	Equal-percentage			8	1.4404, DN15-50	
			M	Modified			9	1.4308	
S	Other		10	1.4408					
			15	1.7379					
2	Seat	X5 Material	1	1.4571	6	Bonnet	X10 Performance	1	Standard
			2	1.4541+Stellite				2	Spring strained
			3	1.4571+PTFE				3	TA-LUFT
			4	1.4057 hard. 35 HRC				4	Bellows
			5	1.4125 hard. 55 HRC					
-	-	X6 Leakage class EN-60534-4	10	1.4571+NBR	7	Packing	X11 Material/Performance	1	PTFE
			33	Other				2	PTFE V
			1	IV Standard				3	PTFE Oxygen
			2	V Enhanced				4	Graphite Braided
-	-	X7 Flow Direction	3	VI Special	5	Graphite Expanded			
			FO	Flow to Open					
			FC	Flow to Close					
3				1.4571, 1.4057 Hardened 35 HRC	8				1.4404+Graphite Spiral
4				1.4404+Graphite Spiral	9				14571+Nitrogen

### VALVE SPECIFICATION


Full specification of the valve consists of:  
**MCV** – symbol  
**-X1-...-X11-** symbols from the table on left  
**PN, DN, Kvs**  
**Medium**  
**Design medium parameters**  
**Shut-off pressure**  
 Example:  
**MCV-C-U-2-P-2-2-FO-1-2-1-5, DN100, PN63, Kvs94.**  
**Medium Water, Td=200°C, Pd=40bar**  
**Shut-off pressure=20bar**  
 It is also recommended to specify working parameters as working pressure, temperature, pressure drop, flow and additional remarks if needed.  
**CAUTION:**  
 The client is not obligated to specify the valve when order. You can simply describe your expectations and INTEC sales person will specify adequate valve for you.



PNEUMATIC	Stroke	F	H	D			Mass
250							
400	25	385	175	305	-	-	20
2x400	25	500	175	305	-	-	40
630	40	485	315	375	-	-	40
2x630	40	715	315	375	-	-	55
1000	60	650	300	480	-	-	70
2x1000	60	920	300	480	-	-	95
ELECTRIC	Stroke	F	M	D	J	K	Mass
XIRa, XIRSa	50	612	318	586	393	322	25
XIRb, XIRsb	50	651	335	602	422	335	34
XIRc, XIRsc	80	841	449	765	490	374	78
XIRa, XIRSa	100	732	318	586	393	322	25
XIRb, XIRsb	100	771	335	602	422	335	34
XIRc, XIRsc	160	991	449	765	490	374	85

Other actuators adaptable. For example AUMA actuators have closely similar dimensions and the same mechanical connections.

PN/DN	Dim.	15	20	25	32	40	50	65	80	100	125	150	200	250	300	
40	LF	130	150	160	180	200	230	290	310	350	400	480	600	730	850	
	LBW	130	150	160	180	200	230	290	310	350	400	480	600	730	850	
	G	107	107	107	114	118	122	166	166	173	248	305	458	475	590	
	GM*	241	241	241	243	253	257	410	410	417	485	510	623	623	735	
	d1	M12x1,25				M16x1,5				M20x1,5				M24x1,5		
63	d2	Ø57,15				Ø84,15				Ø95,25						
	Mass	8	8	8	12	16	22	31	40	65	105	132	195	320	510	
	LF	210	230	230	260	260	300	340	380	430	500	550	650	-	-	
	LBW	160	160	160	230	230	300	340	380	430	500	550	650	-	-	
	G	135	135	135	140	145	155	180	206	217	252	287	439	-	-	
100	GM*	306	306	306	306	306	326	350	375	407	413	426	539	-	-	
	d1	M12x1,25				M16x1,5				M20x1,5						
	d2	Ø57,15				Ø84,15				Ø95,25						
	Mass	9	9	9	13	18	25	33	43	72	101	147	220	-	-	
	LF	210	230	230	260	260	300	340	380	430	500	550	650	-	-	
160	LBW	160	160	160	230	230	300	340	380	430	500	550	650	-	-	
	G	149	149	149	160	172	175	200	233	252	304	365	528	-	-	
	GM*	320	320	320	335	348	345	370	402	442	463	483	615	-	-	
	d1	M12x1,25				M16x1,5				M20x1,5						
	d2	Ø57,15				Ø84,15				Ø95,25						
160	Mass	9	9	9	14	19	28	37	44	75	111	156	243	-	-	



**Zakład Automatyki Przemysłowej INTEC Sp. z o.o.**  
 Bacciarlego 54; 51-649 Wrocław  
 tel./fax +48 71 3481818  
 e-mail: biuro@intec.com.pl  
 http: www.intec.com.pl



**Fabryka Armatury Przemysłowej WAKMET sp. j.**  
 Bodzanów 75, 48-340 Głuchołazy 1  
 tel./fax +48 77 4394020  
 e-mail: wakmet@wakmet.com.pl  
 http: www.wakmet.com.pl